

3CX Compact Small UTM 3

		TCP	UDP	
		Banda	Banda	Jitter
NO VPN	Bridge	829,95 Mbps	808,50 Mbps	0,024 ms
	Nat	606,32 Mbps	616,00 Mbps	0,035 ms
Open VPN	AES128	88,22 Mbps	103,51 Mbps	0,026 ms
	AES256	76,34 Mbps	88,28 Mbps	0,042 ms
	Blowfish	106,81 Mbps	126,28 Mbps	0,040 ms
IPSec	AES128	81,64 Mbps	88,44 Mbps	0,079 ms
	AES256	75,46 Mbps	80,85 Mbps	0,064 ms
	Blowfish 128	76,67 Mbps	78,43 Mbps	0,074 ms
	3DES	41,58 Mbps	44,00 Mbps	0,023 ms

Jitter: In the context of computer networks, jitter is the variation in latency as measured in the variability over time of the packet latency across a network. A network with constant latency has no variation (or jitter).[3] Packet jitter is expressed as an average of the deviation from the network mean latency. However, for this use, the term is imprecise. The standards-based term is "packet delay variation" (PDV).[4] PDV is an important quality of service factor in assessment of network performance.

Deepen jitter: <http://en.wikipedia.org/wiki/Jitter>